




CONTI-AIR[®]
BLANKET TECHNOLOGY

CONTI-AIR[®] PRISMA HC
Sheetfed Blanket

CONTI-AIR® PRISMA HC



Coldset



Heatset



Sheetfed



Packaging



Metaldeco

Das perfekte Drucktuch für den Bogenoffset.

- › Beständig gegen konventionelle, Hybrid- und UV-Farben sowie Waschmittel
- › Verringerter Papierstaubaufbau
- › Minimales Setzverhalten über die gesamte Lebensdauer
- › Hervorragende Knautscherbeständigkeit
- › Sehr gut für Kartondruck / wechselnde Substratdicke

Technische Daten (Nominalwerte)

Farbe:	magenta
Oberfläche:	feinstgeschliffen
Härte Deckgummi:	55° Shore A
Gesamthärte:	78°
Kompressibilität bei 1.350 kPa:	0,220 mm
Dehnung bei 500 N/5 cm:	1,35 %
Dicke:	1,96 mm

The perfect blanket for sheetfed printing.


- › Resistant against conventional, hybrid and UV inks as well as washes
- › Reduced paper dust build up
- › Minimal sinking throughout the lifetime of the printing blanket
- › Excellent smash resistance
- › Very good for carton / changing substrate-thicknesses

Technical Data (Nominal Values)


Color:	magenta
Surface:	microground
Surface hardness:	55° Shore A
Total hardness:	78°
Kompressibilität bei 1.350 kPa:	0.220 mm
Elongation at 500 N/5 cm:	1.35 %
Thickness:	1.96 mm

Unsere Drucktücher verfügen über eine spezielle CONTI-AIR® kompressible Schicht geschlossener Mikrozellen mit Überdruck.

Our printing blankets have a special CONTI-AIR® compressible layer of over-pressured microcells.



mixed application



conventional



ContiTech Elastomer-Beschichtungen GmbH
Breslauer Str. 14 | 37154 Northeim | Germany
service@contiair.com | www.contiair.com

The content of this publication is not legally binding and is provided as information only. The trademarks displayed in this publication are the property of Continental AG and/or its affiliates. Copyright © 2018 ContiTech AG, Hanover. All rights reserved. For complete information go to: www.contitech.de/disc1_en